


Adjustable tip
spacing pipettes



Move It!

Eppendorf Research® plus and Eppendorf Xplorer® plus Move It® adjustable tip spacing pipettes
Fast and secure transfer of multiple samples between different formats

Double Your Performance

Maximizing efficiency

Do you frequently switch between different consumable formats such as tubes to plates? With the Move It pipettes you can easily switch between various formats; reducing your throughput time by 50% while increasing reproducibility.

Safe sample transfer

For a safe sample transfer, the spacing adjustment is vibration-free, easy, and fast. By just a simple turn of the adjustment knob, the tip distance is modified.

1. Maximizing Efficiency

Easy and fast format change

Often, single-channel pipettes are used for multiple sample transfer from one vessel type to another. This can be time-consuming and inconvenient, especially when throughput increases.


Multiple sample transfers between different vessel types and formats become possible with Move It pipettes from Eppendorf. Instead of pipetting many times, four to twelve samples can now be transferred simultaneously. This not only saves you valuable time, it further increases the reproducibility of your results.


Defined settings for quick switches

Switching between source and destination vessels made simple by using the format limiters. These pipettes can easily be adjusted manually with pre-defined settings for different plate formats. All you have to do is to set the format limiters to 384-, 96-, 48-, 24- or 12-well plates using the indicated scale. This enables quick switches back and forth, between two formats, by manually operating the adjustment knob.

Example applications

- > Blood analysis
- > FACS analysis
- > Cell Based Assays
- > Cell Culture
- > ELISA
- > PCR
- > Mouse genotyping







Optimal balance for a relaxed hand

Need a break? With a natural and relaxed hand position the demand for a break decreases. Move It pipettes reduce hand fatigue, as they perfectly balance out in your hand. The user also benefits from convenient visibility of tips and samples. Enjoy a stress-free operation the whole day long.



Rotating pipette head – 360°

All Move It pipettes are designed without the need of tubing. Thus, the pipette head is completely rotatable. The user benefits from comfortable readability of the display. This not only supports an ergonomic and relaxed body posture, it also ensures fast identification of all parameters; saving you valuable time.



2. Safe Sample Transfer

Tubeless system for reliability and reproducible results

The piston-cylinder system is directly connected to the cone. The user therefore benefits from special advantages:

- > Lack of heat transfer to air-cushion from motor or hand – for stable temperature for higher precision and reproducibility
- > Easy autoclavability* – for reduced contamination risk
- > Lack of possible cable tangle and tubing-porosity – for consistently reliable robustness and precision
- > Less maintenance requirements compared to pipettes with tubing system

Adjustment knob for smooth liquid transfer

Since no motor is used, format changes don't cause vibrations enabling liquid transfers without the risk of dripping.


* Xplorer plus lower part and Research plus fully autoclavable



You Have the Choice

Move It

Mechanical Research plus pipettes are the workhorses for each lab. Xplorer plus electronic pipettes are the ideal instrument if you need several pipetting modes (e.g. dispensing or pipetting & mixing) and an additional boost in ergonomics with motor-driven pistons.












* Xplorer plus lower part and Research plus fully autoclavable

More information about MoveIt
www.eppendorf.link/move-it-pipette





Vessel Format	epT.I.P.S.®			epT.I.P.S.® 384	
	Eppendorf Xplorer® plus Move It® Eppendorf Research® plus Move It®			Eppendorf Xplorer® plus Move It® Eppendorf Research® plus Move It®	
	4	6	8	8	12
	300 / 1,200	300 / 1,200	300 / 1,200	20 / 100	20 / 100
Type of tips					
Electronic Pipette					
Mechanical Pipette					
No. of channels					
Volume (µL)					
Tip distance (mm)	9-33	9-20	9-14	4.5-14	4.5-9
384 Wells 				■	■
96 Wells / PCR Tube Strips 	■	■	■	■	■
48 Wells 	■	■	■	■	
24 Wells 	■	■			
12 Wells 	■				
1.5 / 2.0 / 5.0 / 15 mL Tubes 	■				
1.5 / 2.0 / 5.0 / 15 mL Tubes 	■	■			
0.5 / 1.5 / 2.0 mL Tubes 	■	■	■	■	
Agarose gel 	■ *	■ *	■ *	■	■

* Limited suitability due to volume and size of tips



Download our Pipetting eBook
www.eppendorf.link/pipetting-ebook

Eppendorf Research® plus Move It®

(mechanical, multi-channel, variable volume)

No. of channels	Volume	Color code	Order no.
4-channel	30–300 µL	orange	3125 000 150
	120–1,200 µL	dark green	3125 000 184
6-channel	30–300 µL	orange	3125 000 168
	120–1,200 µL	dark green	3125 000 192
8-channel	1–20 µL	light pink	3125 000 117
	5–100 µL	light yellow	3125 000 133
	30–300 µL	orange	3125 000 176
12-channel	120–1,200 µL	dark green	3125 000 206
	1–20 µL	light pink	3125 000 125
	5–100 µL	light yellow	3125 000 141

Eppendorf Xplorer® plus Move It®

(electronic, multi-channel, variable volume, incl. charger)

No. of channels	Volume	Color code	Order no.
4-channel	15–300 µL	orange	4861 000 816
	50–1,200 µL	green	4861 000 833
6-channel	15–300 µL	orange	4861 000 817
	50–1,200 µL	green	4861 000 834
8-channel	1–20 µL	light pink	4861 000 781
	5–100 µL	light yellow	4861 000 794
	15–300 µL	orange	4861 000 818
12-channel	50–1,200 µL	green	4861 000 835
	1–20 µL	light pink	4861 000 782
	5–100 µL	light yellow	4861 000 795

ep Dualfilter T.I.P.S.® 384

Purity grade	Type of packaging	Tip size	Color code	Smallest tip distance	Order no.
Rack (PCR clean, sterile)	ep Dualfilter T.I.P.S.® 384, 3,840 tips (10 racks × 384 tips)	0.1–20 µL	light pink	4.5 mm	0030 078 853
		0.5–100 µL	light yellow	4.5 mm	0030 078 861

ep Dualfilter T.I.P.S.®

Purity grade	Type of packaging	Tip size	Color code	Smallest tip distance	Order no.
Rack (PCR clean, sterile)	ep Dualfilter T.I.P.S.®, 960 tips (10 racks × 96 tips)	20–300 µL	orange	9 mm	0030 078 560
	ep Dualfilter T.I.P.S.®, 480 tips (5 racks × 96 tips)	50–1,250 µL	dark green	9 mm	0030 078 594

> Find the entire product range of tips at www.eppendorf.com/tips



For more information on pipette maintenance,
calibration & adjustment visit:

www.eppendorf.link/pipette-service



Your local distributor: www.eppendorf.com/contact

Eppendorf SE · Barkhausenweg 1 · 22339 Hamburg · Germany
eppendorf@eppendorf.com · www.eppendorf.com

www.eppendorf.com